



High output and repeat accuracy: $\pm 5\%$ and $\pm 3\%$.

Preset torque and automatic shutoff when reaching the set torque. Single-chip intelligent torque control system with LCD display.

With manual 2-speed gearbox, high/low speed can be shifted freely

Very suitable for continuous operation in production assembly and maintenance. Free connection of power handle and drive unit, could be rotated 360°.

Higher efficiency whether tightening or loosening bolts and nuts than hydraulic torque wrench. Portable and durable design, low noise, with overload protection.

After-sales service: 1 year guarantee period, life-long maintenance.

Model	Min torque(N.m)	Max torque(N.m)	Drive S (mm)	D (mm)	L (mm)	K (mm)	M (mm)	Weight (Kg)	Idle speed (rpm)
KSEW-08S	100	800	3/4 "	65	420	205	145	5	30
KSEW-16S	200	1600	1 "	74	460	205	195	6.5	12.2
KSEW-28S	400	2800	1 "	78.5	480	205	215	8.2	6.3
KSEW-40S	700	4200	1 1/2 "	88	500	205	235	9.5	5.1
KSEW-60S	1000	6000	1 1/2 "	113	529	205	264	14.9	2.6
KSEW-80S	1200	8000	1 1/2 "	120	539	205	274	16.8	1.8
KSEW-100S	2000	10000	1 1/2 "	128	555	205	290	18.3	1.5
KSEW-120S	3000	12000	1 1/2 "	128	555	205	290	18.5	1.5

Add: Office No- 114, Dhuri Commerce Plaza, Opp. Vasai Bus Depot

VASAI (E)-401208. Tel : +91 9820656649/ 9021402451

www.spartanengineers.com