



- High output and repeat accuracy: $\pm 5\%$ and $\pm 3\%$.
- Preset torque and automatic shutoff when reaching the set torque.
- Single-chip intelligent torque control system with LCD display.
- With manual 2-speed gearbox, high/low speed can be shifted freely.
- Very suitable for continuous operation in production assembly and maintenance.
- Free connection of power handle and drive unit, could be rotated 360° .
- Higher efficiency whether tightening or loosening bolts and nuts than hydraulic torque wrench.
- Portable and durable design, low noise, with overload protection.
- After-sales service: 1 year guarantee period, life-long maintenance.

| Model | Min.torque (N.m) | Max torque (N.m) | Drive S (mm) | D (mm) | L (mm) | H (mm) | weight (Kg) | Idle speed (rpm) |
|------------------|---------------------|---------------------|-----------------|-------------|------------|------------|----------------|------------------|
| KSEW-08A | 100 | 800 | 3/4 " | 65 | 320 | 249 | 6.6 | 30 |
| KSEW-16A | 200 | 1600 | 1 " | 74 | 320 | 297 | 8.1 | 12.2 |
| KSEW-28A | 400 | 2800 | 1 " | 78.5 | 320 | 317 | 9.8 | 6.3 |
| KSEW-40A | 700 | 4200 | 1 1/2 " | 88 | 320 | 337 | 11.4 | 5.1 |
| KSEW-60A | 1000 | 6000 | 1 1/2 " | 113 | 320 | 366 | 16.5 | 2.3 |
| KSEW-80A | 1200 | 8000 | 1 1/2 " | 120 | 320 | 376 | 18.4 | 1.8 |
| KSEW-100A | 2000 | 10000 | 1 1/2 " | 128 | 320 | 395 | 20 | 1.5 |
| KSEW-120A | 3000 | 12000 | 1 1/2 " | 128 | 320 | 395 | 20.1 | 1.5 |